

Glass Door Reach-in Refrigerators

**Stainless Steel Interior and Front
Digitally Controlled Uniform Temperature**



MSR-23G-1



MSR-49G-2

- **DIGITAL TEMPERATURE CONTROL SYSTEM**
Provides precise and constant temperature. This level of precision allows food products to remain fresh over an extended period of time.
- **HIGH-TECH MONITOR**
The unit will beep if the door has been opened for more than 5 minutes. The monitor digitally displays the present temperature. You can easily change the temperature by adjusting the thermostat.
- **SELF-DIAGNOSTIC SYSTEM**
Displays current status of the refrigerator.
- **AUTOMATIC EVAPORATOR FAN MOTOR DELAYS**
When the door is opened.
- **EFFICIENT REFRIGERATION SYSTEM**
Turbo Air's glass door reach-in refrigerators are designed with over-sized evaporators and condensers for faster cooling and greater efficiency.
- **BOTTOM MOUNT COMPRESSOR**
All units feature a bottom mount compressor for energy savings, high efficiency and easy service.
- **FLUORESCENT INTERIOR LIGHTING**
- **DOUBLE PANE GLASS DOOR WITH HEAT REFLECTING FILM**
- **SELF-CLOSING AND STAY OPEN DOOR FEATURES**
- **HOLDS 33°F ~ 38°F**
- **STANDARD BACKGUARD IMPROVES AIRFLOW**
- **ADJUSTABLE, HEAVY DUTY PVC COATED WIRE SHELVES**
- **SOLID AND STURDY STAINLESS STEEL GRILLE**
- **STAINLESS STEEL INTERIOR INCLUDING TOP AND BOTTOM SURFACE**
- **FOAMED WITH POLYURETHANE, HIGH-DENSITY CELL INSULATION (CFC FREE)**
- **4" SWIVEL CASTERS (STANDARD)**
- **TRAY RACK AVAILABLE**
All models are standard to accept full size door tray racks. Lamp shield must be removed prior to installation and re-assembled after installing racks.

- * A certificated member of NMSDC
- * CEC. California Energy Commission Certificated
- * MEA. City of New York Building Department Approved



Model	Swing Door	CU./FT.	#of Shelves	HP	AMPS	Weight	L D H
MSR-23G-1	1	23	3	1/3	6.5	295	26.8 x 32.2 x 77.6
MSR-49G-2	2	49	6	1/2	11	416	53.9 x 32.2 x 77.6

* Height does not include 5" for caster height.